



# HSM SECURIO B26 - 3.9 mm



## HSM SECURIO B26 document shredder

Data security at the highest level. Thanks to the smooth and powerful cutting system, this document shredder is particularly suitable for data destruction in the workplace or for small working groups.

### Technical data

<b>Order number:</b>	1800111	<b>Intake width:</b>	310 mm
<b>EAN</b>	4026631046268	<b>Container volume / collecting:</b>	55 l
<b>Cutting type:</b>	strip cut	<b>Noise level (idle operation):</b>	ca. 55 dB(A)
<b>Cutting width:</b>	3,9 mm	<b>Weight x Depth x Height:</b>	497 x 397 x 676 mm
<b>Security level (DIN 66399):</b>	E-2   O-2   P-2   T-2	<b>Weight:</b>	24,2 kg
<b>Cutting capacity in sheets 80g/m<sup>2</sup>:</b>	19 - 21	<b>Shredder material:</b>	Paper, Staples and paper clips, Credit card, CD/DVD
<b>Power consumption:</b>	500 W		
<b>Voltage / Frequency:</b>	230 V / 50 Hz		

### Product information



The induction-hardened, solid steel cutting rollers guarantee durability.



The full bin is indicated via the display and the machine switches off automatically.



The device can be intuitively operated with the multifunction element.





### For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



### Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



### High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



### Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



### Display bin full

The full bin is indicated via the display and the machine switches off automatically.



### Filling level indication

The filling level of the waste container can be seen at all times through the inspection window.



[www.huer-engel.de/uz174](http://www.huer-engel.de/uz174)

Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).



\*HSM SECURIO B24, B26, B32

[www.hsm.eu](http://www.hsm.eu)

