

e-STUDIO528P

Datasheet

- > The e-STUDIO528P provides an impressive printing speed of up to 52 pages per minute and a wide range of configuration options for the highest productivity.
- > This A4 monochrome print system impresses with its high productivity with the printout being available after just 4.5 seconds.
- > The large, tiltable colour touch panel gives you easy access to your print jobs and allows you to adjust settings as needed.
- > Whether you print text, graphics or images, your documents will leave a lasting impression.



Efficiency, productivity and functionality are the advantages, which distinguish the e-STUDIO528P. This powerful device meets all the demands for flexibility in the workspace.

A maximum paper capacity of 4,400 sheets can be achieved via the wide range of first class paper handling options. These options allow you to tailor this A4 monochrome print system to your individual requirements and reliably handle even high-volume print jobs.

The e-STUDIO528P meets even the most strict environmental requirements, thanks to its integrated duplex function and efficient energy saving modes, to ensure that valuable resources are used responsibly.

SPECIFICATIONS

General

Print & Copy Speed	52 ppm
Warm-up Time	~ 11 seconds (from sleep mode)
Paper Size & Weight	Cassette: A6-A4/custom, 60-176 g/m ² Bypass: 76 x 127 mm - 216 x 356 mm, 60-176 g/m ²
Paper capacity	Cassette: 1x 550 sheets Bypass: 1x 100 sheets Max.: 4,400 sheets
Inner Output Tray	550-sheet capacity
Automatic Duplex	A6-A4/custom, 60-176 g/m ²
Control Panel	10.9 cm (4.3") colour touch panel
Memory	Standard: 1 GB, max. 5 GB
Interface	10Base-T/100Base-TX/1000Base-T (incl. IPv6), High Speed USB 2.0, WLAN ¹⁾ (IEEE802.11 ac/a/b/g/n)
Dimension & Weight	428 x 510 x 441 mm (W x D x H), ~ 25.6 kg
Starter Kit	Toner and Imaging Unit

Print

Resolution	Max.: 1,200 x 1,200 dpi
First Print Output Time	~ 4.5 seconds
Page Description Language	PCL 6, PCL 5, PostScript 3 and PDF v1.7 emulation, XPS, PPDS
Supported Systems	Windows 10/8/8.1/7, Windows Server 2016/Server 2012/Server 2008 (32/64 bit), Windows Server 2012 R2/ Server 2008 R2 (64 bit), Mac OS X 10.6-10.13, Linux/Unix, Novell NetWare, Citrix, SAP
Mobile Printing	AirPrint, Mopria Print Service, Google Cloud Print
Print Functions	Universal Printer Driver, Print from USB, Print preview, Multiple pages per sheet, Envelope printing

System & Security

Device Management	e-BRIDGE Fleet Management System ¹⁾
System Features	Energy saving modes, Automatic toner saturation/ darkness adjustment
Accounting & Security	Private print, IP address filter, Port filter, Support of SNMPv3, SSL and IPSec protocols, 802.1x authentication ¹⁾ , Operator panel lock, Automatic hard disk wipe ²⁾

Options

2,100-SHEET HIGH CAPACITY FEEDER - KD-1069	1x cassette, 2,100-sheet capacity, A5-A4, 60-135 g/m ²
250-SHEET DRAWER - KD-1065	1x cassette, 250-sheet capacity, A6-A4, 60-176 g/m ² , envelopes
550-SHEET DRAWER - KD-1066	1x cassette, 550-sheet capacity, A6-A4, 60-176 g/m ² , envelopes

250-SHEET LOCKABLE DRAWER - KD-1067	1x cassette, 250-sheet capacity, envelopes, A6-A4, 60-176 g/m ²
550-SHEET LOCKABLE DRAWER - KD-1068	1x cassette, 550-sheet capacity, envelopes, A6-A4, 60-176 g/m ²
250-SHEET DRAWER INSERT - MJ-7004	1x cassette, 250-sheet capacity, envelopes, A6-A4, 60-176 g/m ²
550-SHEET DRAWER INSERT - MJ-7005	1x cassette, 550-sheet capacity, envelopes, A6-A4, 60-176 g/m ²
STAPLE FINISHER - MJ-1045	1x tray, 50-sheet stapling, A5-A4, 75 g/m ² ,
HOLE PUNCH FINISHER - MJ-1046	1x tray, 50-sheet stapling, A5-A4, 75 g/m ² , hole-punch 60-90 g/m ² (2-/3-/4-hole)
4-BIN MAILBOX - MJ-5017	4x trays, 4x 100-sheet capacity, 75 g/m ² , A6-A4/custom
OUTPUT EXPANDER - MJ-5019	500-sheet capacity, 75 g/m ² , envelopes
HIGH CAPACITY OUTPUT EXPANDER - MJ-5018	1,500-sheet capacity, 75 g/m ² , envelopes
SWIVEL CABINET - MH-3100	
ADJUSTABLE PRINTER STAND - KK-3210	
CASTER BASE - KK-4200	
SPACER - KK-4100	
HARD DISK DRIVE - GE-1240	
USER FLASH MEMORY - GC-1420	
MEMORY EXPANSION - GC-1440	
WIRELESS LAN (FRONT MODULE) - GN-1170	
WIRELESS LAN (REAR MODULE) - GN-1190	
SERIAL INTERFACE CARD - GF-1260	
PARALLEL INTERFACE CARD - GF-1250	
FORMS AND BARCODE CARD - GB-2080LXK	
PRESCRIBE CARD - GB-2290LXK	
IPDS Card - GB-2100LXK	



¹⁾ Optional

²⁾ Requires optional HDD

Toshiba Tec Germany Imaging Systems GmbH
Carl-Schurz-Str. 7
41460 Neuss
Germany

Telephone +49 2131-1245-0

Website www.toshibatec.eu

