A3 Black & White Photocopier

BP-20C25 A3 colour MFP that supports the small office environment



- Entry level 25ppm full colour A3 MFPs with 600 x 600 dpi print resolution
- Full-colour network scanning with multiple scan destinations
- Red and green LEDs to notify users of machine/job status from a distance
- * 100-sheet Reversing Single Pass Feeder scans documents at up to $37 \mathrm{ipm^{\star 2}}$
- Sharpdesk Mobile print application^{*3} enables files on a mobile device to be printed
- Direct printing of PDF/TIFF/JPEG files

- Compact, cubic design with the smallest A3 device footprint \star1 in the market
- Tiltable control panel with 4-inch, 5-line mono LCD
- Standard paper tray, as well as multi bypass tray, accommodates a wide variety of paper sizes, including A6 and A3W
- USB port conveniently located at the front of the MFP allowing easy printing from or scanning to the USB drive
- Optional wireless connectivity enables easy access from mobile devices and flexible MFP placement
- ID Card Copy function with dedicated key enables easy copying of both sides of a card onto a single page

*1 'Footprint' refers to the floor or desk space occupied by the device for A3 colour laser MFPs at the time of publishing. *2 Images per minute; when feeding A4 one-sided sheets. *3 Availability varies by country/region.



Specifications

GENERAL

Engine speed Colour ppm (A4)	25
Engine speed B/W ppm (A4)	25
Engine speed Colour ppm (A3)	14
Engine speed B/W ppm (A3)	14
Paper size: MinMax.	A6 - A3W
Paper weight (g/m2)	60 - 256
Paper capacity:Std (sheets)	350
Paper capacity: Max. (sheets)	1850
Warm Up Time (sec.)	29
Memory general min/max (GB)	2
Duplex	STD
Power requirements - rated local AC voltage	220 - 240V, 50 / 60Hz
(Hz)	
Power consumption (kW)	1.84
Dimensions (mm)	560 x 560 x 653
Weight (kg)	52
SCANNER	
	C00 v C00
Resolution (dpi)	600 x 600

FAX

Compression method **Communication protocol** Modem Speed (bps) Document Size (Max)

TONER YIELD

Black (pages at 5% coverage)
Cyan (pages at 5% coverage)
Magenta (pages at 5% coverage)
Yellow (pages at 5% coverage)

MH / MR / MMR / JBIG Super G3 / G3 33600 - 2400 A3

18000 10000 10000 10000

COPIER

Original paper size (Max.) First copy out time B/W (sec.) E-sort Continuous copy (Max. copies) **Resolution Scan (dpi)** Resolution Print (dpi) Gradation (equivalent levels) - B/W Zoom range (%) Preset copy ratios

PRINTER

Resolution (dpi) Interface

Supported OS

PDL emulation printer Std/Opt

WIRELESS LAN

Wireless LAN (Standard / Option) **Compliant regulation** Access mode

Security

A3 8.0 STD 999 600 x 600, 600 x 400 600 x 600 256 25 - 400 10

600 x 600 USB 2.0, 10Base-T / 100Base-TX / 1000Base-T STD: Windows 8.1, 10. Windows Server 2012, 2012R2, 2016, 2019. OPT: Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15 STD: PCL6 OPT: PostScript 3 emulation

OPT IEEE802.11n / g / b Infrastructure mode, Software AP mode WEP, WPA / WPA2-mixed PSK, WPA / WPA2-mixed EAP, WPA2 PSK, WPA2 EAP

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Mac is a trademark of Apple Inc. registered in the US and other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. PCL is a registered trademarks of Hewlett-Packard Company. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation June 2019. Ref:BP-20C25 Datasheet. All trademarks acknowledged. E&OE.

