BP-10C20

A3 colour MFP that supports the small office environment



- Entry level 20ppm full colour A3 MFPs with 600 x 600 dpi print resolution
- Full-colour network scanning with multiple scan destinations
- Red and green LEDs to notify users of machine/job status from a
 dictance.
- USB port conveniently located at the front of the MFP allowing easy printing from or scanning to the USB drive
- Optional wireless connectivity enables easy access from mobile devices and flexible MFP placement
- Direct printing of PDF/TIFF/JPEG files

- Compact, cubic design with the smallest A3 device footprint*1 in the market
- Tiltable control panel with 4-inch, 5-line mono LCD
- Standard paper tray, as well as multi bypass tray, accommodates a wide variety of paper sizes, including A6 and A3W
- ID Card Copy function with dedicated key enables easy copying of both sides of a card onto a single page
- Sharpdesk Mobile print application*² enables files on a mobile device to be printed
- Control and manage networked printers centrally through SRDM (Sharp Remote Device Manager)



^{*1 &#}x27;Footprint' refers to the floor or desk space occupied by the device for A3 colour laser MFPs at the time of publishing. *2 Availability varies by country/region.

Specifications

GENERAL

Engine speed Colour ppm (A4) 20 Engine speed B/W ppm (A4) 20 Engine speed Colour ppm (A3) 12 Engine speed B/W ppm (A3) 12 Paper size: Min.-Max. A6 - A3W Paper weight (g/m2) 60 - 256 Paper capacity:Std (sheets) 350 Paper capacity: Max. (sheets) 1850 Warm Up Time (sec.) 29 Memory general min/max (GB) Duplex STD

Power requirements - rated local AC voltage

(Hz)

Power consumption (kW) 1.84

Dimensions (mm) 560 x 560 x 560

Weight (kg) 47

SCANNER

Resolution (dpi) 600 x 600

WIRELESS LAN

Wireless LAN (Standard / Option) OPT

Compliant regulation IEEE802.11n / g / b
Access mode Infrastructure mode, Software AP

mode

Security WEP, WPA / WPA2-mixed PSK, WPA

/ WPA2-mixed EAP, WPA2 PSK,

WPA2 EAP

220 - 240V, 50 / 60Hz

COPIER

 Original paper size (Max.)
 A3

 First copy out time B/W (sec.)
 8.0

 E-sort
 STD

 Continuous copy (Max. copies)
 999

Resolution Scan (dpi) 600 x 600, 600 x 400

 Resolution Print (dpi)
 600 x 600

 Gradation (equivalent levels) - B/W
 256

 Zoom range (%)
 25 - 400

 Preset copy ratios
 10

PRINTER

Resolution (dpi) 600 x 600

Interface USB 2.0, 10Base-T / 100Base-TX /

1000Base-T

Supported OS STD: Windows 8.1, 10. Windows

Server 2012, 2012R2, 2016, 2019. OPT: Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14,

10.15

PDL emulation printer Std/Opt STD: PCL6 OPT: PostScript 3

emulation

TONER YIELD

 Black (pages at 5% coverage)
 18000

 Cyan (pages at 5% coverage)
 10000

 Magenta (pages at 5% coverage)
 10000

 Yellow (pages at 5% coverage)
 10000

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Mac is a trademark of Apple inc. registered in the US and/or other countries. PCL is a registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. PCL is a registered trademark of Hewlett-Packard Company. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation May 2019. Ref:BP-20C25 Datasheet. All trademarks acknowledged. E&OE.

